

# POWER TRAX - Technical Specifications



## Description

POWER TRAX is a premium tire specially designed for heavy duty service on port trailer, empty container handler or ECH and underground mining machineries. Its deep tread and tough casing provide exceptional durability, minimizing the risk of punctures and accidental damage. POWER TRAX is the ideal tire for hard and tough operations, thanks to the unique tread compound which provides excellent resistance to cuts and chip.

## UM

International Standard

## Construction

 BIAS

## Machinery

Industrial: Empty Container Handler

OTR: Underground Mining Vehicle

Version	STANDARD
Type	TL
Tyre Size	355/65 - 15
LI/SS	170 A5

## Dimensions International Standard

Ply Rating	24
Section Width (mm)	335
Overall Diameter (mm)	830
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2530
Rim Rec	9.75
Tread Depth	28

## Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	7800
25 STEER WHEEL	6000
10 OTHER VEHICLES	7800
25 OTHER VEHICLES	6000
STATIC SIDE LOADER	9060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 20:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..