

AGRIMAX V-FLECTO - Especificações técnicas



Description

AGRIMAX V-FLECTO é a resposta BKT à exigência desafiante em termos de tecnologia e desempenho para tratores de elevada potência. O pneu é perfeito para aplicações de tratamento do terreno e de transporte graças à uma compactação reduzida e ótimas qualidades de autolimpeza. Com a inovadora tecnologia VF, AGRIMAX V-FLECTO permite-lhe transportar cargas muito pesadas a pressões de enchimento inferiores em comparação com pneus standartes e IF alcançando velocidades elevadas. É dotado de Narrow Rim Option (jante estreita) que permite montar jantes standartes. BKT projetou este pneu com geometria otimizada para aumentar o conforto de condução no campo e na estrada reduzindo o consumo de combustível.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Trator de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 46
LI/SS	174 D

Dimensions US Standard

Usa code	94514168
Section Width (inch)	28.1
Overall Diameter (inch)	80.4
Static Loaded Radius (inch)	35.3
Rolling Circumference (inch)	239.8
Rim Rec	DW 25 B
Rim Alt	DW 27 B
ECE	E11-106R-0010941
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	7400	8610	9820	11030	12250	13450
from 40 to 25	8120	9460	10790	12110	13450	14770
20	8290	9640	11000	12360	13710	15070
12	8450	9840	11220	12610	13990	15370
5	8940	10410	11870	13330	14790	16250
*Upto 5 Cyc with front loader	11380	13240	15100	16960	18830	20680
5 HT	8290	9640	11000	12360	13710	15070

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 04:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..