

EARTHMAX SR 41 - Especificações técnicas



Description

O EARTHMAX SR 41 é um pneu radial All Steel, perfeito para caminhões basculantes articulados, carregadoras e escavadoras. Graças à sua estrutura totalmente em aço e ao padrão especial de blocos, o EARTHMAX SR 41 oferece uma excelente resistência contra furos e uma vida útil prolongada. Para além de longas horas de trabalho sem paragens, o pneu garante um conforto extraordinário. O EARTHMAX SR 41 também está disponível em SH-4**** para caminhões basculantes de baixo perfil (LPDT) utilizados em operações de transporte subterrâneo.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora
• Dumper de baixo perfil

Version	STANDARD COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B

Dimensions US Standard

Usa code	94041527
TMPH	161
Overall Width (inch)	26.7
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.5
Rolling Circumference (inch)	202.8
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	E4
Tread Depth	74

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 05:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..