

EM 934 - Dados técnicos



Description

EM 934 foi especialmente projetado para escavadores nas aplicações para a construção das estradas, que proporciona uma excelente tração lateral, bem como extraordinárias qualidades de autolimpagem. O composto de borracha do pneu é especialmente resistente aos cortes e lacerações, enquanto a carcaça robusta assegura uma longa vida operacional.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Escavador

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 - 20	SPECIAL	94054145	E2	146 B	16	7.5	7.0 ; 8.0	11	41.7	19.7	126.3	TT
10.00 - 20	STANDARD	94048601	E2	146 B	16	7.5	7.0 ; 8.0	11	41.7	19.7	126.3	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 05:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..