

MINE STAR - Especificações técnicas



Description

MINE STAR é um pneu de lonas cruzadas, que representa uma ótima escolha de serviço pesado nas minas. O pneu destaca-se pela resistência elevada a cortes/rasgões e perfurações, otimizando a eficiência operacional.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Veículo para minas subterrâneas

Version	STANDARD
Type	TL
Tyre Size	55 X 19.00 - 25

Dimensions US Standard

Usa code	94067879
Ply Rating	50
Section Width (inch)	18.9
Overall Diameter (inch)	55.1
Static Loaded Radius (inch)	24.9
Rolling Circumference (inch)	168.5
Rim Rec	14.00
TRA Code	L5
Tread Depth	87

Load capacity (lbs)

	mph / psi	145
	3	38100
	5	33800
	10	31400
	15	28700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 05:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..