

PORTMAX PT 93 - Especificações técnicas



Description

PORTMAX PT 93 é um pneu para tratores portuários e reboques, especificamente projetado para operações de serviços pesados nos terminais portuários e nos polos logísticos. A mistura especial antiestática do piso garante uma extraordinária resistência ao desgaste e ao calor, também em condições difíceis. PORTMAX PT 93 é ideal para todas as operações que exigem um elevado nível de manobrabilidade, além disso assegura um grip excelente juntamente com uma durabilidade avançada.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Trator portuário • Reboque

Version	INDUSTRIAL
Type	TL
Tyre Size	310/80 R 22.5
LI/SS	175 A8

Dimensions International Standard

Overall Width (mm)	308
Overall Diameter (mm)	1070
Rim Rec	9.00

Load capacity (Kg)

km/h / bar	10.00
40	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 08:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..