

RIB 774 (A) - Especificações técnicas



Description

RIB 774 (A) é um pneu de seção baixa para implementos agrícolas, que proporciona uma capacidade elevada de carga junto com um ciclo de vida prolongado. O pneu é ideal para aplicações com compressores de palha e reboques.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Reboque

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	106 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	288
Rolling Circumference (mm)	1888
Rim Rec	AG 6.75
ECE	E4-106R-002664

Load capacity (Kg)

km/h / bar	5.00
10 FR	1330
25 FR	1130
30 FR	1065
40 FR	950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 20:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..