

## RIDEMAX FL 615 - Dados técnicos



### Description

O RIDEMAX FL 615 é um pneu de flutuação radial adequado para rodas sem tração de atrelados, camiões-cisterna e distribuidores. A estrutura com lonas de cima de aço oferece alta resistência ao furos com maior durabilidade e capacidade de carga elevada. O RIDEMAX FL 615 oferece resistência baixa ao rolamento na estrada com excelentes propriedades de autolimpeza no campo. O formato arredondado e a ampla área de pegada garantem a proteção do solo.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Espalhador • Cisterna móvel • Reboque

| SIZE          | Version      | LI/SS | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW  | OD   | SLR | RC   | SRI | Type | ECE              |
|---------------|--------------|-------|-------------------|--------------------|---------|---------|-----|------|-----|------|-----|------|------------------|
| 800/65 R 32   | STEEL BELTED | 185 D | 185 D             | 185 D              | DW 27 B |         | 830 | 1853 | 834 | 5624 | 875 | TL   | E11-106R-007528  |
| VF800/65 R 32 | STEEL BELTED | 190 D | 190 D             | 190 D              | DW 28 B |         | 815 | 1850 | 811 | 5610 | 875 | TL   | E11-106R-0010408 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 12:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..