

RIDEMAX FL 690 - Dados técnicos



Description

RIDEMAX FL 690 é um pneu radial Flotation e de transporte idóneo para reboques, cisternas móveis e espalhadores. É um pneu principalmente destinado a ser utilizado 75% para aplicações na estrada. Para responder às exigências de cargas mais pesadas na agricultura moderna, a BKT desenhou este pneu com cintos em aço para o tornar forte e cargas muito pesadas, aumentando a produtividade do agricultor. A baixa resistência ao rolamento contribui para uma melhor economia de combustível.

UM

US Standard

Construction



RADIAL

Machinery

Agricultura: Cisterna móvel • Reboque

Industrial: Reboque

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
28L R 26 (750/65 R 26)	STANDARD	94034321	176 A8/173 B	DW 25 B	DW 23 B	28.3	62.6	27.4	186.8	TL	E11-106R-002985
30.5L R 32	STANDARD	94033836	184 A8/181 B	DH 27 B	DW 27 B	31.1	70.9	31.7	213.8	TL	E11-106R-002986
800/60 R 32	STANDARD	94066254	185D	DH 27 B	DW 27 B	31.5	70.9	32.2	214.7	TL	E11-106R-006480
VF 900/65 R 32 (VF35.5LR32)	STANDARD	94067176	197 D	DW 31 B	DW 30 ; TW 30	36.6	78.2	33	231.4	TL	E11-106R-006917

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 07:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..