

SNOW - RIDE (A) - Especificações técnicas



Description

SNOW-RIDE é especialmente apropriado para aplicações carregadoras compactas e minicarregadoras em condições inverniais com pás. O pneu destaca-se pela tração excelente e é ideal para operações na neve e no gelo. O desenho especial do piso do pneu elimina o risco de derrapagens, garantindo um ciclo de vida mais longo do pneu.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Carregadora compacta

Industrial: Minicarregadora

Version	STANDARD
Type	TL
Tyre Size	15.5/60 - 18

Dimensions International Standard

Ply Rating	10
TKPH	1
Section Width (mm)	395
Overall Diameter (mm)	938
Static Loaded Radius (mm)	425
Rolling Circumference (mm)	2814
Rim Rec	W 13
ECE	'E11-106R-005302

Load capacity (Kg)

km/h / bar	2.60
10	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 22:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..