

SNOW - RIDE (B) - Dados técnicos

Description

SNOW-RIDE é especialmente apropriado para aplicações na estrada em condições inverniais com pás carregadoras e tratores de esteira. O pneu destaca-se pela tração excelente e é ideal para operações na neve e no gelo. O desenho especial do piso do pneu elimina os riscos de deslizamento.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Trator de esteira • Carregadora



SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH
16.9 - 24	STANDARD	94043439		12	DW 15 L	DW 14 L	16.9	51.6	23.2	154.7	TL	1
18.4 - 24	STANDARD	94044054		12	DW 16 L	DW 15 L	18.7	54.1	24.6	161	TL	1
15.5 - 25	STANDARD	94048625	L2	12	12.00/1.3		15.6	50.4	22.4	150.3	TL	0
17.5 - 25	STANDARD	94054138	L2	16	14.00/1.5		17.5	53.1	23.9	159.2	TL	0
17.5 - 25	STANDARD	94043446	L2	12	14.00/1.5		17.5	53.1	23.9	159.2	TL	0
20.5 - 25	STANDARD	94044399	L2	16	17.00/2.0	17.00/1.7	21.1	58.7	25.7	174.1	TL	0
23.5 - 25	STANDARD	94047918	L2	16	19.50/2.5		24.1	64.2	27.3	189	TL	0

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 22:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..