

TR 136 - Especificações técnicas



Description

TR 136 foi desenvolvido pela BKT para ser utilizado com tratores e reboques nas operações para trabalhar a terra e para o transporte. O pneu assegura uma tração superior em todas as condições operacionais junto com uma ótima resistência a todo o tipo de corte, reduzindo o tempo de paragem da máquina e aumentando a sua produtividade. Graças ao maior número de blocos, TR 136 fornece uma excelente tração, também com cargas elevadas.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator • Reboque

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 30
LI/SS	140 A8

Dimensions US Standard

Usa code	94004232
Ply Rating	12
Section Width (inch)	16.9
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	27
Rolling Circumference (inch)	178.1
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-003010
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	5520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 06:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..