

TR 171 - Especificações técnicas



Description

TR 171 é um pneu com piso profundo, apropriado para tratores para trabalhar a terra. Graças às propriedades de autolimpagem extraordinárias, o pneu é ideal para terrenos húmidos e molhados. Desenvolvido com um composto de borracha especial, TR 171 garante uma tração e uma duração excelentes, também em condições operacionais mais duras.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 9.5 - 20 |
| LI/SS | 101 A6 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 6 |
| Section Width (mm) | 241 |
| Overall Diameter (mm) | 955 |
| Static Loaded Radius (mm) | 449 |
| Rolling Circumference (mm) | 2942 |
| Rim Rec | W 8 |
| Rim Alt | W 7 |
| ECE | E11-106R-003359 |
| TRA Code | R1W+ |

Load capacity (Kg)

| km/h / bar | 2.10 |
|------------|------|
| 30 | 825 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 09:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..