

TR 171 - Especificações técnicas



Description

TR 171 é um pneu com piso profundo, apropriado para tratores para trabalhar a terra. Graças às propriedades de autolimpagem extraordinárias, o pneu é ideal para terrenos húmidos e molhados. Desenvolvido com um composto de borracha especial, TR 171 garante uma tração e uma duração excelentes, também em condições operacionais mais duras.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Trator

Version	HD
Type	TT
Tyre Size	9.5 - 20
LI/SS	107 A6

Dimensions International Standard

Ply Rating	8
TKPH	1
Section Width (mm)	241
Overall Diameter (mm)	955
Static Loaded Radius (mm)	449
Rolling Circumference (mm)	2942
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-004105
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	2.80
30	975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 09:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..