

TR 459 - Especificações técnicas



Description

TR 459 foi projetado especificadamente para operações de escavação e carga, bem como para aplicações no setor da municipalidade e na manutenção com tratores e retroescavadoras. O pneu proporciona uma estabilidade elevada e está disponível em duas versões. A versão "special" garante um ciclo de vida prolongado do pneu.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Retroescavadora • Trator
Industrial: Retroescavadora

Version	INDUSTRIAL
Type	TL
Tyre Size	17.5L - 24
LI/SS	148 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	445
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	557
Rolling Circumference (mm)	3825
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-004659
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.70
40	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18/05/2025 04:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..