

## TR 461 - Especificações técnicas



### Description

TR 461 é um pneu BKT desenvolvido para as aplicações em obras municipais e na manutenção com tratores, bem como para as operações de carga com levantadores telescópicos. A proteção do flanco é caracterizada pela resistência especial a cortes e lacerações, que garante uma vida mais longa do pneu, mesmo em superfícies duras junto com uma estabilidade excelente.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Industrial: Retroescavadora • Levantador telescópico •  
Trator

|           |          |
|-----------|----------|
| Version   | STANDARD |
| Type      | TL       |
| Tyre Size | 21L - 24 |
| LI/SS     | 157 A8   |

## Dimensions International Standard

|                            |         |
|----------------------------|---------|
| Ply Rating                 | 14      |
| Section Width (mm)         | 540     |
| Overall Diameter (mm)      | 1385    |
| Static Loaded Radius (mm)  | 607     |
| Rolling Circumference (mm) | 4072    |
| Rim Rec                    | DW 18 L |
| TRA Code                   | R4      |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.50 |
| 40         | 4125 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/05/2025 09:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..