

XL GRIP PLUS - Especificações técnicas



Description

XL GRIP PLUS (L-4) foi concebido especificadamente para carregadores. O piso profundo assegura uma ótima resistência a cortes e furos, além de um ciclo de vida prolongado do pneu. XL GRIP PLUS é apropriado particularmente para operações de serviço pesadas.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: Trator de esteira • Carregadora

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	760
Overall Diameter (mm)	1915
Static Loaded Radius (mm)	876
Rolling Circumference (mm)	5709
Rim Rec	25.00/3.5
TRA Code	L4
Tread Depth	60

Load capacity (Kg)

km/h / bar	4.25
10	17500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/05/2025 04:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..