

RIDEMAX FL 615 - Technical Specifications



Description

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel belted structure offers high puncture resistant with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on road with outstanding self-cleaning properties on the field. The rounded shoulder and wide footprint area ensure soil protection.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STEEL BELTED
Type	TL
Tyre Size	800/65 R 32
LI/SS	185 D
LI/SS DRIVE WHEEL	185 D
LI/SS FREE ROLLING	185 D

Dimensions US Standard

Usa code	94070176
Section Width (inch)	32.7
Overall Diameter (inch)	73
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	221.4
Rim Rec	DW 27 B
ECE	E11-106R-007528

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	87
40	8770	9590	11630	12850	14890	16930	18560	20390
30	10610	11610	14080	15550	18020	20490	22460	24680
25	11930	13040	15820	17480	20250	23030	25240	27730
20	13250	14480	17560	19410	22490	25570	28030	30800
15	13860	15140	18370	20300	23520	26750	29320	32220
5	15780	17260	20930	23130	26800	30470	33410	36700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 18:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..