

# RIDEMAX FL 693 M - Technical Specifications



## Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	710/45 R 22.5
LI/SS	165 D

# Dimensions International Standard

Section Width (mm)	706
Overall Diameter (mm)	1212
Static Loaded Radius (mm)	542
Rolling Circumference (mm)	3658
SRI (mm)	575
Rim Rec	AG 24.00
ECE	E11-106R-005994

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1715	1925	2390	2720	3140	3565	3890	4265	4685
65	1880	2115	2630	2990	3455	3915	4275	4690	5150
50	2280	2560	3180	3620	4180	4740	5180	5675	6235
40	2560	2875	3575	4065	4695	5325	5815	6375	7005
30	2840	3190	3970	4515	5215	5915	6460	7080	7780
25	2975	3340	4155	4725	5455	6190	6760	7410	8140
10	3385	3805	4730	5380	6215	7050	7695	8440	9270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 18:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..