

RIDEMAX IT 696 - Technical Specifications



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	420/65 R 24 IND
LI/SS	146 D/151 A8

Dimensions International Standard

TKPH	1
Section Width (mm)	418
Overall Diameter (mm)	1158
Static Loaded Radius (mm)	530
Rolling Circumference (mm)	3483
SRI (mm)	550
Rim Rec	DW 13 L; W13
Rim Alt	DW 15 L ; DW 14 L
ECE	E11-106R-005952

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1200	1470	1650	1950	2220	2490	2730	3000
50	1295	1590	1780	2105	2400	2690	2950	3240
40	1380	1690	1900	2245	2555	2865	3140	3450
30	1440	1765	1980	2340	2665	2990	3275	3600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 30/04/2025 20:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..