

AGRIMAX SPARGO - Specificații tehnice



Descriere

AGRIMAX SPARGO este anvelopa specială BKT pentru aplicații de culturi pe rânduri. A fost concepută pentru creșterea productivității pe câmp și pentru conservarea solului pe termen lung. Datorită tehnologiei VF, anvelopa oferă o capacitate de încărcare mai mare la presiunea standard. Datorită carcasi puternice și unui număr mare de caneluri, AGRIMAX SPARGO asigură o durabilitate remarcabilă împreună cu o stabilitate puternică atât pe câmp, cât și în timpul transferurilor rutiere.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	VF 380/85 R 38
LI/SS	161 D

Dimensiuni US Standard

Usa code	94045303
Lățimea secțiunii (inch)	15
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	190.2
Rim Rec	W 13 A
Rim Alt	W 12
ECE	E4-106R-001482
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	46
45	5470	6120	6670	7050	7320	7600	7880	8250	8620	8900	9270
From 40 to 25	6010	6730	7350	7750	8050	8360	8670	9080	9480	9790	10200
20	6130	6860	7480	7900	8210	8530	8830	9250	9660	9980	10400
12	6250	6990	7630	8060	8370	8690	9010	9440	9860	10180	10610
5	6620	7400	8070	8510	8860	9190	9530	9980	10420	10760	11210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17.05.2025 23:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..