

## AS 2001 - Fișa de date



### Descriere

AS 2001 este o anvelopă care are cute încrucișate care se potrivește cel mai bine tractoarelor în operațiunile de cultivare a solului. Designul său oferă proprietăți excelente de tracțiune și auto-curățare. AS 2001 este fabricată dintr-un compus special rezistent la tăiere și așchiere, care asigură și o capacitate mare de încărcare.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor

| SIZE      | Version  | TRA Code | LI/SS  | PR | RIM REC | RIM ALT | SW  | OD   | SLR | RC   | SRI | Type | ECE              |
|-----------|----------|----------|--------|----|---------|---------|-----|------|-----|------|-----|------|------------------|
| 9.5 - 22  | STANDARD | R1       | 110 A6 | 8  | W 8     | W 7     | 243 | 1007 | 470 | 3074 |     | TT   | E11-106R-0010508 |
| 18.4 - 26 | STANDARD | R1       | 142 A6 | 10 | W 16 L  | W 15 L  | 467 | 1475 | 650 | 4250 | 675 | TT   | E11-106R-003367  |
| 18.4 - 26 | STANDARD | R1       | 142 A6 | 10 | W 16 L  | W 15 L  | 467 | 1475 | 650 | 4250 | 675 | TL   | E11-106R-003367  |
| 18.4 - 26 | STANDARD | R1       | 146 A6 | 12 | W 16 L  | W 15 L  | 467 | 1475 | 650 | 4250 | 675 | TT   | E11-106R-003507  |
| 18.4 - 26 | STANDARD | R1       | 146 A6 | 12 | W 16 L  | W 15 L  | 467 | 1475 | 650 | 4250 | 675 | TL   | E11-106R-003507  |
| 18.4 - 26 | STANDARD | R1       | 149 A6 | 14 | W 16 L  | W 15 L  | 467 | 1475 | 650 | 4250 | 675 | TT   | E11-106R-003598  |
| 16.9 - 28 | SPECIAL  | R1       | 143 A6 | 12 | W 15 L  | W 14 L  | 429 | 1420 | 651 | 4319 | 675 | TT   | E11-106R-004345  |
| 16.9 - 28 | STANDARD | R1       | 135 A6 | 8  | W 15 L  | W 14 L  | 429 | 1420 | 651 | 4319 | 675 | TT   | E11-106R-003508  |
| 16.9 - 28 | STANDARD | R1       | 139 A6 | 10 | W 15 L  | W 14 L  | 429 | 1420 | 651 | 4319 | 675 | TT   | E11-106R-004344  |
| 16.9 - 28 | STANDARD | R1       | 143 A6 | 12 | W 15 L  | W 14 L  | 429 | 1420 | 651 | 4319 | 675 | TT   | E4-106R-002045   |
| 16.9 - 28 | STANDARD | R1       | 143 A6 | 12 | W 15 L  | W 14 L  | 429 | 1420 | 651 | 4319 | 675 | TL   | E4-106R-002045   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17/05/2025 05:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..