

AW 702 - Specificații tehnice



Descriere

AW 702 a fost dezvoltată pentru utilaje, remorci și prese de balotat în aplicații de cultivare a solului și transport. Această anvelopă pentru sarcini grele a fost proiectată de BKT pentru a oferi un nou nivel de durabilitate. AW 702 este disponibilă în diferite versiuni pentru a satisface nevoile specifice ale utilizatorului final: o versiune cu "bandă de aramidă" este disponibilă pentru cei care au nevoie de o rezistență sporită la perforare, versiunea "HD" are un compus special rezistent la tăiere și așchiere, în timp ce versiunea "specială" oferă o rezistență extraordinară la miriște.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare •
Remorcă
Industrial: Remorcă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	10.0/75 - 15.3
LI/SS FREE ROLLING	119 A8

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	274
Overall Diameter (mm)	760
Static Loaded Radius (mm)	351
Rolling Circumference (mm)	2213
Rim Rec	9.00

Load capacity (Kg)

km/h / bar	3.10
10 FR	1905
25 FR	1620
30 FR	1525
40 FR	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17/05/2025 6:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..