

AW 702 - Specificații tehnice



Descriere

AW 702 a fost dezvoltată pentru utilaje, remorci și prese de balotat în aplicații de cultivare a solului și transport. Această anvelopă pentru sarcini grele a fost proiectată de BKT pentru a oferi un nou nivel de durabilitate. AW 702 este disponibilă în diferite versiuni pentru a satisface nevoile specifice ale utilizatorului final: o versiune cu "bandă de aramidă" este disponibilă pentru cei care au nevoie de o rezistență sporită la perforare, versiunea "HD" are un compus special rezistent la tăiere și așchiere, în timp ce versiunea "specială" oferă o rezistență extraordinară la miriște.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare •
Remorcă
Industrial: Remorcă

Versiune	ARAMID BELTED
Tip	TL
Dimensiunea anvelopei	11.5/80 - 15.3
LI/SS FREE ROLLING	139 A8

Dimensiuni Standard internațional

Rating de sarcină	14
Lățimea secțiunii (mm)	297
Overall Diameter (mm)	844
Static Loaded Radius (mm)	370
Rolling Circumference (mm)	2473
Rim Rec	9.00
ECE	E11-106R-004548

Load capacity (Kg)

km/h / bar	4.75
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17.05.2025 09:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..