

AW 702 - Specificații tehnice



Descriere

AW 702 a fost dezvoltată pentru utilaje, remorci și prese de balotat în aplicații de cultivare a solului și transport. Această anvelopă pentru sarcini grele a fost proiectată de BKT pentru a oferi un nou nivel de durabilitate. AW 702 este disponibilă în diferite versiuni pentru a satisface nevoile specifice ale utilizatorului final: o versiune cu "bandă de aramidă" este disponibilă pentru cei care au nevoie de o rezistență sporită la perforare, versiunea "HD" are un compus special rezistent la tăiere și așchiere, în timp ce versiunea "specială" oferă o rezistență extraordinară la miriște.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare •
Remorcă
Industria: Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	13.0/75 - 16
LI/SS FREE ROLLING	135 A8

Dimensiuni Standard internațional

Rating de sarcină	10
Lățimea secțiunii (mm)	340
Overall Diameter (mm)	890
Static Loaded Radius (mm)	396
Rolling Circumference (mm)	2726
Rim Rec	11.0
Rim Alt	9 ; W 9 ; W 11
ECE	E4-106R-001899

Load capacity (Kg)

km/h / bar	3.00
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17.05.2025 01:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..