

FL 252 - Specificații tehnice



Descriere

FL 252 este o anvelopă potrivită pentru aplicațiile de recoltare a fânului cu mașini de întors fânul/fânătoare, precum și pentru operațiuni logistice cu stivuitoare. Această anvelopă oferă o durabilitate excelentă, în timp ce modelul specific al benzii de rulare asigură stabilitate maximă în timpul operațiunilor de ridicare.

UM

US Standard

Construcție

BIAS

Mașinării

Agricultură: Mașină de întors fânul/Fânător
Industrial: Stivuator

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	7.00 - 12

Dimensiuni US Standard

Usa code	94006892
Rating de sarcină	14
Lăţimea secţiunii (inch)	7.6
Overall Diameter (inch)	26.9
Rim Rec	5.00 S

Load capacity (lbs)

mph / psi	131
15 LOAD WHEEL	6075
15 STEER WHEEL	4675
5 OTHER VEHICLES	6075
15 OTHER VEHICLES	4675
STATIC SIDE LOADER	7055

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17.05.2025 01:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..