

IT 400 - Specificații tehnice



Descriere

IT 400 este o anvelopă cu model de nervuri potrivită pentru șosea, pentru platforme joase în aplicații de transport. Anvelopa este potrivită pentru aplicații de mare viteză și oferă economii semnificative de combustibil.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Remorcă cu platformă joasă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	10.00 - 15
LI/SS	137/133 J

Dimensiuni Standard internațional

Rating de sarcină	14
Lățimea secțiunii (mm)	274
Overall Diameter (mm)	925
Static Loaded Radius (mm)	408
Rolling Circumference (mm)	2747
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
ECE	E11-54R-0018587

Load capacity (Kg)

km/h / bar	7.60	6.90	6.20
15	3680	-	-
30	-	3035	-
100 LS	-	2300	-
100 LD	-	-	2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 18.05.2025 02:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..