

PUDDLE SPECIAL (A) - Specificații tehnice



Descriere

PUDDLE SPECIAL este o anvelopă agricolă R-2 special concepută pentru operațiuni pe câmpurile de orez. Designul foarte adânc al benzii de rulare, împreună cu modelul special de caneluri, oferă cea mai bună aderență și tracțiune excelentă chiar și pe sol umed și moale. Bara centrală lată oferă o adaptabilitate mai bună pentru aplicațiile rutiere și oferă performanțe extraordinare de service. În plus, PUDDLE SPECIAL prezintă caracteristici superioare de auto-curățare și durabilitate excelentă.

UM

US Standard

Construcție

❖ BIAS

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	12.4 - 28
LI/SS	137 A2

Dimensiuni US Standard

Usa code	94059461
Rating de sarcină	12
Lățimea secțiunii (inch)	12.8
Overall Diameter (inch)	54.5
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	160.1
Rim Rec	W 11
Rim Alt	W 10
TRA Code	R2+

Load capacity (lbs)

mph / psi	52
5	5080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 19.05.2025 02:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..