

TR 117 - Specificații tehnice



Descriere

TR 117 este ideală pentru aplicații de irigare cu irigatoare pivot. Modelul său special conceput oferă tracțiune excelentă și proprietăți de auto-curățare remarcabile.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Instalații de irigare tip pivot

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	14.9 - 24
LI/SS	112 A6

Dimensiuni Standard internațional

Rating de sarcină	4
Lățimea secțiunii (mm)	378
Overall Diameter (mm)	1245
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3660
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E4-106R-002026
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.80	1.05
30	1120	---
CREEP	---	2175

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 19/05/2025 01:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..