

## TR 128 - Specificații tehnice



### Descriere

TR 128 a fost special concepută pentru tractoare utilitare și motocultoare. Designul lat și adânc și compusul special de rezistență la tăiere și aşchiere asigură o durată de viață extinsă a anvelopei. TR 128 oferă tracțiune maximă pe sol umed.

### UM

US Standard

### Construcție

✚ BIAS

### Mașinării

Agricultură: Timon • Vehicul universal

|                       |             |
|-----------------------|-------------|
| Versiune              | STANDARD    |
| Tip                   | TT          |
| Dimensiunea anvelopei | 180/85 D 12 |
| LI/SS                 | 63 A6       |

## Dimensiuni US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94058129        |
| Rating de sarcină            | 4               |
| Lăţimea secţiunii (inch)     | 6.5             |
| Overall Diameter (inch)      | 24.1            |
| Static Loaded Radius (inch)  | 11.6            |
| Rolling Circumference (inch) | 72.7            |
| Rim Rec                      | 5 JA            |
| ECE                          | E11-106R-004821 |

## Load capacity (lbs)

|           |     |
|-----------|-----|
| mph / psi | 23  |
| 20        | 600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17/05/2025 01:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..