

TR 270 - Specificații tehnice



Descriere

TR 270 este o anvelopă de tractor potrivită pentru aplicații de cultivare a solului. Este special concepută pentru a oferi performanțe maxime pe sol umed și ud. În aceste condiții de sol, este necesară o anvelopă care oferă o aderență superioară și caracteristici îmbunătățite de auto-curățare. TR 270 îndeplinește perfect toate aceste caracteristici.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	23.1 - 34
LI/SS	145 A8

Dimensiuni US Standard

Usa code	94004935
Rating de sarcină	8
Lăţimea secţiunii (inch)	23.2
Overall Diameter (inch)	72.8
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	217.8
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R2

Load capacity (lbs)

mph / psi	16
25	6400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/17/2025 1:36 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..