

TR 318 - Specificații tehnice



Descriere

TR 318 este proiectat special pentru pulverizatoare și utilaje. Canelurile sale cu două unghiuri oferă o tracțiune excelentă și un confort remarcabil la condus. TR 318 are, de asemenea, proprietăți extraordinare de auto-curățare.

UM

Standard internațional

Construcție

✚ BIAS

Mașinării

Agricultură: Mașini de implementare • Pulverizator

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	26 X 10.00 - 12
LI/SS	107 A3

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	265
Overall Diameter (mm)	675
Rim Rec	8.5
ECE	E11-106R-004522

Load capacity (Kg)

km/h / bar	3.70
15	975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 19/05/2025 01:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..