

## VIJETA - Specificații tehnice



### Descriere

VIJETA este o anvelopă agricolă potrivită atât pentru aplicații pe șosea, cât și pentru off-road. Modelul cu 5 nervuri optimizează distribuția sarcinii. În plus, compusul rezistent la uzură și carcasa puternică asigură un ciclu lung de viață al anvelopei.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Remorcă

|                       |           |
|-----------------------|-----------|
| Versiune              | STANDARD  |
| Tip                   | TT        |
| Dimensiunea anvelopei | 8.00 - 19 |

## Dimensiuni Standard internațional

|                        |      |
|------------------------|------|
| Rating de sarcină      | 10   |
| Lățimea secțiunii (mm) | 225  |
| Overall Diameter (mm)  | 912  |
| Rim Rec                | 5.00 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 5.15 |
| 15         | 1660 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 19/05/2025 3:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..