

XL GRIP PLUS - Specificații tehnice



Descriere

XL GRIP PLUS (L-4) a fost special concepută pentru încărcătoare. Banda de rulare adâncă oferă rezistență ridicată la tăiere și la perforare, precum și un ciclu de viață extins al anvelopei. XL GRIP PLUS este potrivită în special pentru lucrări în condiții dificile.

UM

US Standard

Construcție

✚ BIAS

Mașinării

OTR: Buldozer • Încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	29.5 - 25

Dimensiuni US Standard

Usa code	94059577
Rating de sarcină	36
Overall Width (inch)	29.9
Overall Diameter (inch)	75.4
Static Loaded Radius (inch)	34.5
Rolling Circumference (inch)	224.8
Rim Rec	25.00/3.5
TRA Code	L4
Tread Depth	75

Load capacity (lbs)

mph / psi	83
5	46100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17/05/2025 03:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..