

XL GRIP PLUS - Fișa de date



Descriere

XL GRIP PLUS (L-4) a fost special concepută pentru încărcătoare. Banda de rulare adâncă oferă rezistență ridicată la tăiere și la perforare, precum și un ciclu de viață extins al anvelopei. XL GRIP PLUS este potrivită în special pentru lucrări în condiții dificile.

UM

US Standard

Construcție

❖ BIAS

Mașinării

OTR: Buldozer • Încărcător

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
26.5 - 25	STANDARD	94033331	L4	28	22.00/3.0		27.2	69.9	32.1	206.8	TL	72
26.5 - 25	STANDARD	94044856	L4	32	22.00/3.0		27.2	69.9	32.1	206.8	TL	72
29.5 - 25	STANDARD	94033584	L4	28	25.00/3.5		29.9	75.4	34.5	224.8	TL	75
29.5 - 25	STANDARD	94044863	L4	32	25.00/3.5		29.9	75.4	34.5	224.8	TL	75
29.5 - 25	STANDARD	94059577	L4	36	25.00/3.5		29.9	75.4	34.5	224.8	TL	75
35/65 - 33	STANDARD	94064762	L4	42	28.00/3.5		35.4	81.9	0	0	TL	79

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 17.05.2025 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..