

ROCK GRIP IND4 (ECH) - Technical Specifications



Description

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) is a bias-ply tire designed for Empty container handler in several applications including industrial handling and steelworks. The special ROCK GRIP compound ensure particular heat resistance along with great stability and durability.

UM

International Standard

Construction



Machinery

Industrial: Empty Container Handler

Version	PORT INDUSTRIAL
Туре	TL
Tyre Size	16.00 - 25

Dimensions International Standard

Ply Rating	36
Overall Width (mm)	470
Overall Diameter (mm)	1525
Static Loaded Radius (mm)	699
Rolling Circumference (mm)	4514
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	18360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 02:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..