

## ROCK GRIP (T) - Data Sheet



### Description

ROCK GRIP (E-4) best suits on/off trucks in quarries and short-haul mining applications to carry heavy loads. The special tread compound minimizes cuts and punctures on roughest ground conditions. ROCK GRIP (E-4) offers exceptional traction and an extended tire life-cycle.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

OTR: On/Off Truck • Rigid Dump Truck

SIZE	Version	USACode	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
10.00 - 20	STANDARD	94050802	18	7.5	7.0	11	42.9	0	0	TT	39
11.00 - 20	STANDARD	94062416	18	8.0	7.5	11.8	44.7	0	0	TT	43
12.00 - 20	STANDARD	94070114	20	8.5	8.0	12.4	46.1	0	0	TT	42
12.00 - 24	STANDARD	94035601	18	8.5	8.0	12.4	49.8	23.4	147.8	TT	42
12.00 - 24	STANDARD	94035755	20	8.5	8.0	12.4	49.8	23.4	147.8	TT	42

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 00:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..