

БК 6060 - Технические спецификации



Description

Шины БК 6060 подходят для прицепов и экскаваторов-погрузчиков при их эксплуатации как в поле, так и на дороге, а также при выполнении землеройных и погрузочных работ. Эти шины с блочным рисунком протектора имеют долгий срок службы.

UM

International Standard

Construction

✚ BIAS

Machinery

Производство: экскаватор-погрузчик • Прицеп

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	265
Overall Diameter (mm)	925
Static Loaded Radius (mm)	432
Rolling Circumference (mm)	2847
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004362

Load capacity (Kg)

km/h / bar	7.25
30	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 7:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..