

COLT - Технические спецификации



Description

COLT - шины с блочным рисунком протектора для прицепов и легких грузовиков, используемых для перевозок как по дороге, так и по полям. Прочность и другие характеристики шин COLT остаются на высоком уровне на всем протяжении срока эксплуатации.

UM

International Standard

Construction

✚ BIAS

Machinery

Сельское хозяйство: Малотоннажный грузовик • Прицеп
Производство: Прицеп

Version	INDUSTRIAL
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	212
Overall Diameter (mm)	820
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (Kg)

km/h / bar	8.40
40	1840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 3:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..