

GF 304 - Технические спецификации



Description

Шины GF 304 подходят для сельскохозяйственной техники и траншеекопателей, используемых для обработки почвы. Независимо от того, какую операцию по обработке почвы вы выполняете, шины GF 304 гарантируют наивысший комфорт оператора и эффективную защиту почвы от повреждений. Шины GF 304 также предлагаются с брекером из арамидного волокна в версии «Aramid-belted», которая гарантирует высокое сопротивление проколам.

UM

International Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Гольфкарт

Version	STANDARD
Type	TL
Tyre Size	18 X 8.50 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	216
Overall Diameter (mm)	460
Static Loaded Radius (mm)	202
Rolling Circumference (mm)	1334
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003442

Load capacity (Kg)

km/h / bar	1.50
15	375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 0:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..