

LIFT STAR PLUS - Загрузить лист технических данных



Description

LIFT STAR PLUS - это диагональные шины, разработанные специально для телескопических погрузчиков, используемых в тяжелых строительных работах и прочих трудоемких видах работ. Низкий профиль боковины этих шин обеспечивает отличную устойчивость при подъемных работах, тогда как ненаправленный рисунок протектора допускает эксплуатацию шин в различных видах монтажных работ. К тому же, специально разработанная боковина этих шин гарантирует дополнительную защиту от порезов и проколов.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Телескопический погрузчик

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
370/75 - 28	STANDARD	14	11.00		365	1270	583	3851	TL	E11-106R-005331
400/75 - 28	STANDARD	16	12.00 GR		400	1318	592	3944	TL	E11-106R-005330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 5:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..