

MUD POWER HD - Технические спецификации



Description

Грузовая шина MUD POWER HD была разработана специально для использования на погрузчиках с бортовым поворотом. Глубокий рисунок протектора и грунтозацепные канавки особой формы обеспечивают превосходное сцепление как на мокром, так и на сыпучем грунте. Благодаря специальному составу резиновой смеси и прочному каркасу шина MUD POWER HD получила увеличенный срок службы даже при интенсивной эксплуатации в тяжелых условиях.

UM

International Standard

Construction

❖ BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	268
Overall Diameter (mm)	800
Rim Rec	8.25
TRA Code	R4

Load capacity (Kg)

km/h / bar	5.20
10	2135
15	1685
25	1560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 0:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..