

PL 846 - Загрузить лист технических данных



Description

Шины PL 846 специально разработаны для сельскохозяйственной техники, используемой при обработке почвы. Они отличаются исключительной устойчивостью и великолепными тяговыми характеристиками, а также высокой стойкостью к порезам и разрывам. Шины PL 846 идеально подходят для эксплуатации на каменистых поверхностях.

UM

US Standard

Construction



Machinery

Сельское хозяйство: Сельскохозяйственное оборудование

| SIZE | Version | USACode | PR | RIM REC | RIM ALT | SW | OD | Туре |
|----------|----------|----------|----|---------|---------|-----|------|------|
| 6.00 - 9 | STANDARD | 94032143 | 10 | 4.00 E | | 6.3 | 21.3 | TT |
| 6.00 - 9 | STANDARD | 94035915 | 12 | 4.00 E | | 6.3 | 21.3 | TT |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 18.05.2025 3:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..