

PORT KING PLUS - Загрузить лист технических данных



Description

Шины PORT KING PLUS созданы специально для контейнерных погрузчиков, используемых для интермодальных/логистических операций. Глубокий рисунок протектора с крупными грунтозацепами наряду с особой резиновой смесью обеспечивают более продолжительный срок службы шины. Они также доступны в версии с канавками из специальной резиновой смеси, стойкой к образованию трещин (GCRC).

UM

US Standard

Construction

 BIAS

Machinery

Производство: Контейнерный погрузчик

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
18.00 - 25	GCRC	94026593	IND4	40	13.00 /2.5	15.00/2.5	20.8	65.9	30.1	195.1	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17.05.2025 8:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..