

RIDEMAX FL 693 M - Технические спецификации



Description

693 M RIDEMAX FL — это идеальные радиальные шины для тех, кто часто использует прицепы/автоцистерны для дорожных перевозок. Шины RIDEMAX FL 693 M разработаны для преимущественного использования на дорогах (75 % времени эксплуатации). Они демонстрируют великолепные характеристики при эксплуатации на дорогах и отличные свойства самоочистения, при этом обеспечивая также высокий уровень комфорта. Индекс скорости «D/E» означает возможность эксплуатации шин на более высоких скоростях, что приводит к значительной экономии времени. Низкое сопротивление качению способствует снижению расхода топлива, а усиленные борты и стальной брекер повышают долговечность.

UM

International Standard

Construction

RADIAL

Machinery

Сельское хозяйство: Автоцистерна • Прицеп

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	161 D/158 E

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1244
Static Loaded Radius (mm)	549
Rolling Circumference (mm)	3767
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	16.00 ; 17.00 ; AG 20.00
ECE	E4-106R-000630

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1555	1745	2170	2465	2850	3230	3530	3870	4250
65	1690	1900	2360	2685	3100	3515	3840	4210	4625
50	2050	2300	2860	3250	3755	4260	4650	5100	5600
40	2300	2580	3210	3650	4215	4785	5225	5725	6290
25	2670	3000	3730	4240	4900	5560	6070	6655	7310
10	3040	3415	4250	4830	5580	6330	6910	7580	8325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 5:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..