

## ROCK GRIP E4 - Технические спецификации



### Description

ROCK GRIP (E-4) - это диагональные шины, специально созданные для грузовиков, которые используются для горных работ и разработок карьеров. Если условия вашей работы требуют от шины высокой степени термостойкости и защиты от порезов, ROCK GRIP станет вашим надежным партнером.

### UM

US Standard

### Construction

 BIAS

### Machinery

Производство: Самосвал с жесткой рамой

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

## Dimensions US Standard

Usa code	94041886
Ply Rating	24
Overall Width (inch)	14.8
Overall Diameter (inch)	55.5
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	164.3
Rim Rec	10.00/2.0
TRA Code	E4
Tread Depth	64

## Load capacity (lbs)

mph / psi	83
30	11400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 6:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..