

SNOW RIDE - PLUS - Технические спецификации



Description

Шина SNOW RIDE - PLUS оптимально подходит для погрузчиков с бортовым поворотом при эксплуатации на дорогах в зимних условиях. Она обладает превосходными тягово-сцепными характеристиками на снегу и на льду. Специальный рисунок протектора уменьшает вероятность пробуксовки.

UM

International Standard

Construction

❖ BIAS

Machinery

Производство: Погрузчик

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions International Standard

Ply Rating	16
Section Width (mm)	525
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	656
Rolling Circumference (mm)	4370
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
TRA Code	L2

Load capacity (Kg)

km/h / bar	3.50
10	8250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 4:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..