

TR 128 - Технические спецификации



Description

Шины TR 128 специально разработаны для тракторов общего назначения и почвофрез. Широкие и глубокие грунтозацепы и специальная резиновая смесь, устойчивая к порезам и разрывам, обеспечивают увеличенный срок службы. Шины TR 128 характеризуются максимальной тягой на мокрой почве.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Почвофреза • Универсальный автомобиль

Version	STANDARD
Type	TT
Tyre Size	6.00 - 12
LI/SS	76 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	160
Overall Diameter (mm)	635
Static Loaded Radius (mm)	296
Rolling Circumference (mm)	1926
Rim Rec	4.00 E
Rim Alt	4.00 E DT
ECE	E11-106R-003479

Load capacity (Kg)

km/h / bar	2.60
30	400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 3:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..