

TR 171 - Технические спецификации



Description

TR 171 — это шины с глубоким рисунком протектора, подходящие для тракторов, используемых при обработке почвы. Благодаря выдающимся свойствам самоочищения эти шины идеально подходят для эксплуатации на влажной и сырой почве. Шины TR 171 изготовлены из специальной резиновой смеси, что обеспечивает великолепную тягу и потрясающую прочность в условиях уборочных работ.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор-тягач

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 9.5 - 22 |
| LI/SS | 110 A6 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 8 |
| Section Width (mm) | 244 |
| Overall Diameter (mm) | 1005 |
| Static Loaded Radius (mm) | 472 |
| Rolling Circumference (mm) | 3107 |
| Rim Rec | W 8 |
| Rim Alt | W 7 |
| ECE | E11-106R-003490 |
| TRA Code | R1W+ |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 3.00 |
| 30 | 1060 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 2:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..