

## TR 317 - Технические спецификации



### Description

TR 317 — это шины, подходящие для сельскохозяйственной техники, траншекопателей и садовых комбайнов, используемых в муниципальных работах и при обработке почвы. Шины TR 317 имеют большую площадь пятна контакта, что обеспечивает превосходное сцепление и выдающуюся устойчивость в любых условиях, а также отличное самоочищение.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •  
Машина для сбора фруктов • Траншейный экскаватор

Version	HD
Type	TL
Tyre Size	18 X 8.50 - 8

## Dimensions US Standard

Usa code	94045884
Ply Rating	6
Section Width (inch)	8.5
Overall Diameter (inch)	17.7
Static Loaded Radius (inch)	7.8
Rolling Circumference (inch)	51.4
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90

## Load capacity (lbs)

mph / psi	34
10	1050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19.05.2025 7:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..